

## Integral Bonnet Needle Valves


**Part No.**


SS-26VF8

**Part Description**

Stainless Steel Integral Bonnet Needle Valve, 0.73 Cv, 1/2 in. FNPT, Vee Stem

## Specifications

General	
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/2 in.
Connection 1 Type	Female NPT
Connection 2 Size	1/2 in.
Connection 2 Type	Female NPT
eClass (4.1)	37010201
eClass (5.1.4)	37010201
eClass (6.0)	37-01-02-03
eClass (6.1)	37-01-02-03
Flow Pattern	Straight (2-way)
Handle Color	Not Applicable
Handle Style	Stainless Steel Bar
Lubricant	Perf. Polyether/Tung. Disulfide (WL7)
Max Temperature with Pressure Rating	450°F @ 4130 PSIG /232°C @ 284 BAR
Orifice	0.250 in
Packing	PFA
Room Temperature Pressure Rating	6000 PSIG @ 100°F /413 BAR @ 37°C
Stem Tip Material	316 Stainless Steel
Stem Type	Vee
UNSPSC (10.0)	40141602
UNSPSC (11.0501)	40141602
UNSPSC (13.0601)	40141602
UNSPSC (15.1)	40141602
UNSPSC (4.03)	40141602
UNSPSC (SWG01)	40141602
Valve Material	Stainless Steel

 The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

 Caution: Do not mix or interchange valve components with those of other manufacturers.