

Lift Check Valves


Part No.

SS-58F8

Part Description

Stainless Steel Lift Check Valve, 2.20 Cv, 1/2 in. FNPT

Specifications

General

Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	1/2 in.
Connection 1 Type	Female NPT
Connection 2 Size	1/2 in.
Connection 2 Type	Female NPT
eClass (4.1)	37010801
eClass (5.1.4)	27300400
eClass (6.0)	27-29-20-01
eClass (6.1)	27-29-20-01
Lubricant	Nickel Never Seez
Max Temperature Pressure Rating	400°F @ 4280 PSIG /204°C @ 294 BAR
Room Temperature Pressure Rating	4600 PSIG @ 100°F /316 BAR @ 37°C
Surface Finish	Standard
Testing	No Optional Testing
UNSPSC (10.0)	40141634
UNSPSC (11.0501)	40141634
UNSPSC (13.0601)	40141634
UNSPSC (15.1)	40141659
UNSPSC (4.03)	40141601
UNSPSC (SWG01)	40141601
Valve Material	316 Stainless Steel

! The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

⚠ Caution: Do not mix or interchange valve components with those of other manufacturers.