

Poppet Check Valves


Part No.


SS-CHF12-1

Part Description

Stainless Steel Poppet 4600 psig (316 bar) Check Valve, 3/4 in. FNPT, 1 psig (0.07 bar)

Specifications

General	
Backup Ring Material	PTFE
Body Material	316 Stainless Steel
Cleaning Process	Standard Cleaning and Packaging (SC-10)
Connection 1 Size	3/4 in.
Connection 1 Type	Female NPT
Connection 2 Size	3/4 in.
Connection 2 Type	Female NPT
Cracking Pressure	1 psi (0.07 bar, 0.007 MPa)
eClass (4.1)	37010801
eClass (5.1.4)	27300400
eClass (6.0)	27-30-06-01
eClass (6.1)	27-30-06-01
Feature	O-rings: Fluorocarbon FKM
Lubricant	Christo-lube MCG 111 (WL8)
Max Temperature Pressure Rating	400°F @ 3560 PSIG /204°C @ 245 BAR
Room Temperature Pressure Rating	4300 PSIG @ 100°F /296 BAR @ 37°C
Seal Material	Fluorocarbon FKM
Spring Coating	None
Surface Finish	Standard
Testing	No Optional Testing
UNSPSC (10.0)	40141641
UNSPSC (11.0501)	40141641
UNSPSC (13.0601)	40141641
UNSPSC (15.1)	40141641
UNSPSC (4.03)	40141601
UNSPSC (SWG01)	40141641
Valve Material	316 Stainless Steel

 The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.

 Caution: Do not mix or interchange valve components with those of other manufacturers.